Pict Snip: Build Snips from Picts

Version 8.14.0.1

July 9, 2024

```
(require pict/snip)
                             package: pict-snip-lib
The pict/snip library constructs snip% instances that draw based on a given pict? object.
 pict-snip% : class?
   superclass: snip%
 (new pict-snip% [pict pict]) \rightarrow (is-a?/c pict-snip%)
   pict : pict?
     Creates a pict-snip% object, using pict to draw.
(send a-pict-snip get-pict) \rightarrow pict?
     Returns the pict passed to the constructor.
 (send a-pict-snip get-extent dc
                                   У
                                   W
                                   descent
                                   1space
                                   rspace) \rightarrow void?
   dc : (is-a?/c dc<%>)
   x : real?
   w : (or/c (box/c (and/c real? (not/c negative?))) #f)
```

h : (or/c (box/c (and/c real? (not/c negative?))) #f)

descent : (or/c (box/c (and/c real? (not/c negative?))) #f)
lspace : (or/c (box/c (and/c real? (not/c negative?))) #f)
rspace : (or/c (box/c (and/c real? (not/c negative?))) #f)

Updates the arguments based on the size of the pict returned from get-pict.

```
(send a-pict-snip draw dc
                        У
                        left
                        top
                        right
                        bottom
                        dx
                        dy
                        draw-caret) \rightarrow void?
 dc: (is-a?/c dc<%>)
 x : real?
 y : real?
 left : real?
 top : real?
 right : real?
 bottom : real?
 dx : real?
 dy : real?
 draw-caret : (or/c 'no-caret 'show-inactive-caret 'show-caret
                      (cons/c exact-nonnegative-integer?
                              exact-nonnegative-integer?))
```

Overrides draw in snip%.

Draws the pict returned from get-pict.

```
(send a-pict-snip write f) \rightarrow void? f: (is-a?/c editor-stream-out%)
```

Uses a record-dc% to write the way that the result of get-pict draws and saves that to f.

```
(send a-pict-snip copy) \rightarrow (is-a?/c pict-snip%)
```

Returns a snip that has the same pict as this one.

```
snipclass : (is-a?/c snip-class%)
```

The snip-class% instance used by instances of pict-snip%.

```
reader : (is-a?/c snip-reader<%>)
```

The snip-reader<%> instance used by the wxme library.