

# Scheme: Compatibility Libraries and Executables

Version 9.1.0.1

January 15, 2026

Racket was once called “PLT Scheme,” and a number of libraries with names starting `scheme` provide compatibility with the old name. A few old executables are also provided.

Do not use `#lang scheme` to start new projects; `#lang racket` is the preferred language.

## Contents

|           |                                   |           |
|-----------|-----------------------------------|-----------|
| <b>1</b>  | <code>scheme</code>               | <b>6</b>  |
| <b>2</b>  | <code>scheme/base</code>          | <b>7</b>  |
| <b>3</b>  | <code>scheme/async-channel</code> | <b>8</b>  |
| <b>4</b>  | <code>scheme/bool</code>          | <b>9</b>  |
| <b>5</b>  | <code>scheme/class</code>         | <b>10</b> |
| <b>6</b>  | <code>scheme/cmdline</code>       | <b>11</b> |
| <b>7</b>  | <code>scheme/contract</code>      | <b>12</b> |
| <b>8</b>  | <code>scheme/control</code>       | <b>13</b> |
| <b>9</b>  | <code>scheme/date</code>          | <b>14</b> |
| <b>10</b> | <code>scheme/dict</code>          | <b>15</b> |
| <b>11</b> | <code>scheme/file</code>          | <b>16</b> |
| <b>12</b> | <code>scheme/fixnum</code>        | <b>17</b> |
| <b>13</b> | <code>scheme/flonum</code>        | <b>18</b> |
| <b>14</b> | <code>scheme/foreign</code>       | <b>19</b> |
| <b>15</b> | <code>scheme/function</code>      | <b>20</b> |
| <b>16</b> | <code>scheme/future</code>        | <b>21</b> |

|           |                                   |           |
|-----------|-----------------------------------|-----------|
| <b>17</b> | <code>scheme/generator</code>     | <b>22</b> |
| <b>18</b> | <code>scheme/gui</code>           | <b>23</b> |
| <b>19</b> | <code>scheme/gui/base</code>      | <b>24</b> |
| <b>20</b> | <code>scheme/gui/dynamic</code>   | <b>25</b> |
| <b>21</b> | <code>scheme/help</code>          | <b>26</b> |
| <b>22</b> | <code>scheme/include</code>       | <b>27</b> |
| <b>23</b> | <code>scheme/init</code>          | <b>28</b> |
| <b>24</b> | <code>scheme/language-info</code> | <b>29</b> |
| <b>25</b> | <code>scheme/list</code>          | <b>30</b> |
| <b>26</b> | <code>scheme/load</code>          | <b>31</b> |
| <b>27</b> | <code>scheme/local</code>         | <b>32</b> |
| <b>28</b> | <code>scheme/match</code>         | <b>33</b> |
| <b>29</b> | <code>scheme/math</code>          | <b>34</b> |
| <b>30</b> | <code>scheme/mpair</code>         | <b>35</b> |
| <b>31</b> | <code>scheme/nest</code>          | <b>36</b> |
| <b>32</b> | <code>scheme/package</code>       | <b>37</b> |
| <b>33</b> | <code>scheme/path</code>          | <b>38</b> |

|    |                                       |    |
|----|---------------------------------------|----|
| 34 | <code>scheme/port</code>              | 39 |
| 35 | <code>scheme/pretty</code>            | 40 |
| 36 | <code>scheme/promise</code>           | 41 |
| 37 | <code>scheme/provide</code>           | 42 |
| 38 | <code>scheme/provide-syntax</code>    | 43 |
| 39 | <code>scheme/provide-transform</code> | 44 |
| 40 | <code>scheme/require</code>           | 45 |
| 41 | <code>scheme/require-syntax</code>    | 46 |
| 42 | <code>scheme/require-transform</code> | 47 |
| 43 | <code>scheme/runtime-config</code>    | 48 |
| 44 | <code>scheme/runtime-path</code>      | 49 |
| 45 | <code>scheme/sandbox</code>           | 50 |
| 46 | <code>scheme/serialize</code>         | 51 |
| 47 | <code>scheme/set</code>               | 52 |
| 48 | <code>scheme/signature</code>         | 53 |
| 49 | <code>scheme/shared</code>            | 54 |
| 50 | <code>scheme/splicing</code>          | 55 |

|    |                                      |    |
|----|--------------------------------------|----|
| 51 | <code>scheme/string</code>           | 56 |
| 52 | <code>scheme/struct-info</code>      | 57 |
| 53 | <code>scheme/stxparam</code>         | 58 |
| 54 | <code>scheme/stxparam-exptime</code> | 59 |
| 55 | <code>scheme/surrogate</code>        | 60 |
| 56 | <code>scheme/system</code>           | 61 |
| 57 | <code>scheme/tcp</code>              | 62 |
| 58 | <code>scheme/trait</code>            | 63 |
| 59 | <code>scheme/udp</code>              | 64 |
| 60 | <code>scheme/unit</code>             | 65 |
| 61 | <code>scheme/unit-exptime</code>     | 66 |
| 62 | <code>scheme/unsafe/ops</code>       | 67 |
| 63 | <code>scheme/vector</code>           | 68 |
| 64 | <code>mred</code>                    | 69 |
| 65 | Compatibility Executables            | 70 |

## 1 `scheme`

```
(require scheme)      package: scheme-lib
```

The `scheme` library re-exports `racket`, except based on `scheme/base` instead of `racket/base`, the `struct` and `struct/ctc` from `scheme/unit` is exported, `scheme/set` is not re-exported, `scheme/system` is not re-exported, `pretty-print` is re-directed in as `scheme/pretty`, and `scheme/nest` is re-exported.

## 2 `scheme/base`

```
(require scheme/base)      package: scheme-lib
```

The `scheme/base` library re-exports `racket/base`, except that `racket`'s `struct`, `hash`, `hasheq`, `hasheqv`, `in-directory`, and `local-require` are not exported, and `make-base-namespace`, `make-base-empty-namespace` `#%module-begin` are different.

```
| (make-base-empty-namespace) → namespace?
```

Like `make-base-empty-namespace` from `racket/base`, but with `scheme/base` attached.

```
| (make-base-namespace) → namespace?
```

Like `make-base-namespace` from `racket/base`, but with `scheme/base` attached.

```
| (#%module-begin form ...)
```

Like `#%module-begin` from `racket/base`, but declares a `configure-runtime` submodule that uses `scheme/runtime-config` instead of `racket/runtime-config`, and it does not check for an immediate declaration of `configure-runtime` among the *forms*.

### 3 `scheme/async-channel`

```
(require scheme/async-channel)
```

package: `scheme-lib`

The `scheme/async-channel` library re-exports `racket/async-channel`.



## 4 `scheme/bool`

```
(require scheme/bool)      package: scheme-lib
```

The `scheme/bool` library re-exports `racket/bool`.

## 5 `scheme/class`

```
(require scheme/class)           package: scheme-lib
```

The `scheme/class` library re-exports `racket/class`, except that `writable<%>` is exported under the name `printable<%>` (and `printable<%>` from `racket/class` is not exported).

```
| printable<%> : interface?
```

An alias for `writable<%>`.

## 6 `scheme/cmdline`

```
(require scheme/cmdline)      package: scheme-lib
```

The `scheme/cmdline` library re-exports `racket/cmdline`.

## 7 `scheme/contract`

```
(require scheme/contract)      package: scheme-lib
```

The `scheme/contract` library re-exports `racket/contract`.

## 8 `scheme/control`

```
(require scheme/control)      package: scheme-lib
```

The `scheme/control` library re-exports `racket/control`.

## 9 `scheme/date`

```
(require scheme/date)      package: scheme-lib
```

The `scheme/date` library re-exports `racket/date`.

## 10 `scheme/dict`

```
(require scheme/dict)      package: scheme-lib
```

The `scheme/dict` library re-exports `racket/dict`.

## 11 `scheme/file`

```
(require scheme/file)      package: scheme-lib
```

The `scheme/file` library re-exports `racket/file`.



## 12 `scheme/fixnum`

```
(require scheme/fixnum)      package: scheme-lib
```

The `scheme/fixnum` library re-exports `racket/fixnum`.

## 13 `scheme/flonum`

```
(require scheme/flonum)      package: scheme-lib
```

The `scheme/flonum` library re-exports `racket/flonum`.

## 14 `scheme/foreign`

```
(require scheme/foreign)      package: scheme-lib
```

The `scheme/foreign` library re-exports `ffi/unsafe`, `ffi/unsafe/cvector`, and `ffi/vector`, except that `unsafe!` must be used to import the unsafe bindings of `ffi/unsafe` and `ffi/unsafe/cvector`.

```
(unsafe!)
```

Makes unsafe bindings available.

```
(provide* provide-star-spec ...)  
provide-star-spec = (unsafe id)  
                    | (unsafe (rename-out [id external-id]))  
                    | provide-spec
```

Like `provide`, but `ids` under `unsafe` are not actually provided. Instead, they are collected for introduction into an importing module via a macro created by `define-unsafes`.

```
(define-unsafes id)
```

Cooperates with `provide*` to define `id` as a `unsafe!`-like form that introduces definitions for each binding provided as `unsafe`. The `define-unsafes` form must occur after all the `provide*` forms to which it refers.

## 15 `scheme/function`

```
(require scheme/function)      package: scheme-lib
```

The `scheme/function` library re-exports `racket/function`.

## 16 `scheme/future`

```
(require scheme/future)      package: scheme-lib
```

The `scheme/future` library re-exports `racket/future`.

## 17 `scheme/generator`

```
(require scheme/generator)      package: scheme-lib
```

The `scheme/generator` library re-exports `racket/generator`.

## 18 `scheme/gui`

```
(require scheme/gui)      package: gui-lib
```

The `scheme/gui` library re-exports `racket/gui`, except that it builds on `scheme/gui/base` instead of `racket/gui/base`.

## 19 `scheme/gui/base`

```
(require scheme/gui/base)      package: gui-lib
```

The `scheme/gui/base` library re-exports `racket/gui/base`, except that it builds on `scheme` instead of `racket`.

```
| (make-gui-empty-namespace) → namespace?
```

Like `make-base-empty-namespace`, but with `scheme/class` and `scheme/gui/base` also attached to the result namespace.

```
| (make-gui-namespace) → namespace?
```

Like `make-base-namespace`, but with `scheme/class` and `scheme/gui/base` also required into the top-level environment of the result namespace.



## 20 `scheme/gui/dynamic`

```
(require scheme/gui/dynamic)      package: scheme-lib
```

The `scheme/gui/dynamic` library re-exports `racket/gui/dynamic`, except that `gui-dynamic-require` extracts bindings from `mred` instead of `scheme/gui/base`.

```
(gui-dynamic-require sym) → any  
  sym : symbol?
```

Like `gui-dynamic-require` from `racket/gui/base`, but to access exports of `scheme/gui/base`.

## 21 `scheme/help`

```
(require scheme/help)      package: scheme-lib
```

The `scheme/help` library re-exports `racket/help`.

## 22 `scheme/include`

```
(require scheme/include)      package: scheme-lib
```

The `scheme/include` library re-exports `racket/include`.

## 23 `scheme/init`

```
(require scheme/init)      package: scheme-lib
```

The `scheme/init` library re-exports `racket/init`, except that it builds on `scheme` instead of `racket`.

## 24 `scheme/language-info`

```
(require scheme/language-info)           package: scheme-lib
```

The `scheme/language-info` library is like `racket/language-info`, except that it produces `'(#(scheme/runtime-config configure #f))` for the `'configure-runtime` information key.

See also `scheme/runtime-config`.

## 25 `scheme/list`

```
(require scheme/list)      package: scheme-lib
```

The `scheme/list` library re-exports `racket/list`.

## 26 `scheme/load`

```
(require scheme/load)      package: scheme-lib
```

The `scheme/load` library re-exports `racket/load`.

## 27 `scheme/local`

```
(require scheme/local)      package: scheme-lib
```

The `scheme/local` library re-exports `racket/local`.



## 28 `scheme/match`

```
(require scheme/match)      package: scheme-lib
```

The `scheme/match` library re-exports `racket/match`.

## 29 `scheme/math`

```
(require scheme/math)      package: scheme-lib
```

The `scheme/math` library re-exports `racket/math`.

## 30 `scheme/mpair`

```
(require scheme/mpair)      package: compatibility-lib
```

The `scheme/mpair` library re-exports `compatibility/mlist`.

## 31 `scheme/nest`

```
(require scheme/nest)      package: scheme-lib
```

```
| (nest ([datum ...+] ...) body ...+)
```

Combines nested expressions that syntactically drift to the right into a more linear textual format, much in the same way that `let*` linearizes a sequence of nested `let` expressions.

For example,

```
(nest ([let ([x 10]
             [y 6]])
      [with-handlers ([exn:fail? (lambda (x) 15)])]
      [parameterize ([current-output-port (current-error-port)])]
      [let-values ([d r] (quotient/remainder x y))])
      (display (+ d r)))
```

is equivalent to

```
(let ([x 10]
      [y 6])
  (with-handlers ([exn:fail? (lambda (x) 15)])
    (parameterize ([current-output-port (current-error-port)])
      (let-values ([d r] (quotient/remainder x y))
        (display (+ d r))))))
```

The `nest` form is unusual in that it has no semantics apart from its expansion, and its implementation is easier to understand than a precise prose description:

```
(define-syntax nest
  (syntax-rules ()
    [(nest () body0 body ...)
     (let () body0 body ...)]
    [(nest ([form forms ...]) body0 body ...)
     (form forms ... (let () body0 body ...))]
    [(nest ([form forms ...] . more) body0 body ...)
     (form forms ... (nest more body0 body ...))]))
```

## 32 `scheme/package`

```
(require scheme/package)      package: compatibility-lib
```

The `scheme/package` library re-exports `compatibility/package`.

### 33 `scheme/path`

```
(require scheme/path)      package: scheme-lib
```

The `scheme/path` library re-exports `racket/path`.

## 34 `scheme/port`

```
(require scheme/port)      package: scheme-lib
```

The `scheme/port` library re-exports `racket/port`.

## 35 `scheme/pretty`

```
(require scheme/pretty)      package: scheme-lib
```

The `scheme/pretty` library re-exports `racket/pretty`, except that `pretty-write` is exported under the name `pretty-print` (and `pretty-print` from `racket/pretty` is not exported).

```
(pretty-print v [port]) → void?  
  v : any/c  
  port : output-port? = (current-output-port)
```

An alias for `pretty-write`.



## 36 `scheme/promise`

```
(require scheme/promise)      package: scheme-lib
```

The `scheme/promise` library re-exports `racket/promise`.

## 37 `scheme/provide`

```
(require scheme/provide)      package: scheme-lib
```

The `scheme/provide` library re-exports `racket/provide`.

## 38 `scheme/provide-syntax`

```
(require scheme/provide-syntax)      package: scheme-lib
```

The `scheme/provide-syntax` library re-exports `racket/provide-syntax`.

## 39 `scheme/provide-transform`

```
(require scheme/provide-transform)      package: scheme-lib
```

The `scheme/provide-transform` library re-exports `racket/provide-transform`.

## 40 `scheme/require`

```
(require scheme/require)      package: scheme-lib
```

The `scheme/require` library re-exports `racket/require`.

## 41 `scheme/require-syntax`

```
(require scheme/require-syntax)      package: scheme-lib
```

The `scheme/require-syntax` library re-exports `racket/require-syntax`.

## 42 `scheme/require-transform`

```
(require scheme/require-transform)    package: scheme-lib
```

The `scheme/require-transform` library re-exports `racket/require-transform`.

## 43 `scheme/runtime-config`

```
(require scheme/runtime-config)      package: scheme-lib
```

The `scheme/runtime-config` library is like `racket/runtime-config`, except that its `configure` sets `print-as-expression` to `#f`.



## 44 `scheme/runtime-path`

```
(require scheme/runtime-path)      package: scheme-lib
```

The `scheme/runtime-path` library re-exports `racket/runtime-path`.

## 45 scheme/sandbox

```
(require scheme/sandbox)      package: sandbox-lib
```

The `scheme/sandbox` library re-exports `racket/sandbox`, except that `sandbox-namespace-specs`, `make-evaluator`, and `make-module-evaluator` are replaced.

```
(sandbox-namespace-specs) → (cons/c (-> namespace?)
                                     (listof module-path?))
(sandbox-namespace-specs spec) → void?
spec : (cons/c (-> namespace?)
               (listof module-path?))
```

Like `sandbox-namespace-specs` from `racket/sandbox`, but the default is `(list make-base-namespace)` if `gui?` is `#f`, `(list make-gui-namespace)` if `gui?` is `#t`.

```
(make-evaluator language
                 input-program ...
                 #:requires requires
                 #:allow-read allow) → (any/c . -> . any)
language : (or/c module-path?
              (list/c 'special symbol?)
              (cons/c 'begin list?))
input-program : any/c
requires : (listof (or/c module-path? path?))
allow : (listof (or/c module-path? path?))
(make-module-evaluator module-decl
                       #:language lang
                       #:allow-read allow) → (any/c . -> . any)
module-decl : (or/c syntax? pair?)
lang : (or/c #f module-path?)
allow : (listof (or/c module-path? path?))
```

Like `make-evaluator` and `make-module-evaluator` from `racket/sandbox`, but the value of the `sandbox-namespace-specs` parameter is installed as the value of `sandbox-namespace-specs` from `racket/sandbox` before chaining to `make-evaluator` and `make-module-evaluator` from `racket/sandbox`.

## 46 `scheme/serialize`

```
(require scheme/serialize)      package: scheme-lib
```

The `scheme/serialize` library re-exports `racket/serialize`.

## 47 `scheme/set`

```
(require scheme/set)      package: scheme-lib
```

The `scheme/set` library re-exports `racket/set`.

## 48 `scheme/signature`

```
(require scheme/signature)      package: scheme-lib
```

The `scheme/signature` library re-exports `racket/signature`.

## 49 `scheme/shared`

```
(require scheme/shared)      package: scheme-lib
```

The `scheme/shared` library re-exports `racket/shared`.

## 50 `scheme/splicing`

```
(require scheme/splicing)      package: scheme-lib
```

The `scheme/splicing` library re-exports `racket/splicing`.

## 51 `scheme/string`

```
(require scheme/string)      package: scheme-lib
```

The `scheme/string` library re-exports `racket/string`.



## 52 `scheme/struct-info`

```
(require scheme/struct-info)      package: scheme-lib
```

The `scheme/struct-info` library re-exports `racket/struct-info`.

## 53 `scheme/stxparam`

```
(require scheme/stxparam)      package: scheme-lib
```

The `scheme/stxparam` library re-exports `racket/stxparam`.

## 54 `scheme/stxparam-exptime`

```
(require scheme/stxparam-exptime)      package: scheme-lib
```

The `scheme/stxparam-exptime` library re-exports `racket/stxparam-exptime`.

## 55 `scheme/surrogate`

```
(require scheme/surrogate)      package: scheme-lib
```

The `scheme/surrogate` library re-exports `racket/surrogate`.

## 56 `scheme/system`

```
(require scheme/system)      package: scheme-lib
```

The `scheme/system` library re-exports `racket/system`.

## 57 `scheme/tcp`

```
(require scheme/tcp)      package: scheme-lib
```

The `scheme/tcp` library re-exports `racket/tcp`.

## 58 `scheme/trait`

```
(require scheme/trait)      package: scheme-lib
```

The `scheme/trait` library re-exports `racket/trait`.

## 59 `scheme/udp`

```
(require scheme/udp)      package: scheme-lib
```

The `scheme/udp` library re-exports `racket/udp`.



## 60 `scheme/unit`

```
(require scheme/unit)      package: scheme-lib
```

The `scheme/unit` library re-exports `racket/unit`, except that `struct` and `struct/ctc` are from `mzlib/unit` instead of `struct` from `racket/base` and `struct/ctc` from `racket/unit`.

## 61 `scheme/unit-exptime`

```
(require scheme/unit-exptime)      package: scheme-lib
```

The `scheme/unit-exptime` library re-exports `racket/unit-exptime`.

## 62 `scheme/unsafe/ops`

```
(require scheme/unsafe/ops)      package: scheme-lib
```

The `scheme/unsafe/ops` library re-exports `racket/unsafe/ops`.

## 63 `scheme/vector`

```
(require scheme/vector)      package: scheme-lib
```

The `scheme/vector` library re-exports `racket/vector`.

## 64 mred

```
(require mred)      package: gui-lib
```

The `mred` library is like `scheme/gui/base`, except that it provides variants of `make-gui-namespace` and `make-gui-empty-namespace` that attach `mred` instead of `scheme/gui/base`.

Both `scheme/gui/base` and `racket/gui/base` depend on `mred`, so it is attached by all variants of `make-gui-empty-namespace`.

```
(require mred/mred)  package: gui-lib
```

The `mred` library actually just re-exports `mred/mred`, which is an even older name for the library.

## 65 Compatibility Executables

The following executables are included in the Racket distribution for compatibility with older versions of Racket:

- `mzscheme` — the same as `racket -I scheme/init`
- `mred` — the same as `gracket -I scheme/gui/init`
- `drscheme` — the same as `drracket`
- `mzc` — an old interface to some of the tools provided by `raco`, including `raco make` and `raco ctool`; use `mzc --help` for more information
- `plt-help` — the same as `raco docs`