Slideshow: Figure and Presentation Tools

Version 9.4.0.5

Matthew Flatt
and Robert Bruce Findler

November 15, 2026

Slideshow is a library for creating presentation slides. Unlike Powerpoint, Slideshow provides no WYSIWYG interface for constructing slides. Instead, like Beamer, a presentation is generated by a program.

To get started, run the `slideshow` executable, and click the Run Tutorial link.

To learn more about Slideshow, see also "Slideshow: Functional Presentations" [Findler06].

`#lang slideshow` package: `slideshow-lib`

Most of the bindings defined in the manual are provided by the `slideshow` language, which also re-exports all of `racket` except for `printable<%>` (due to backward-compatibility issues) and all of `pict`.

Contents

1 Creating Slide Presentations **4**

1.1 Slide Basics 4

1.2 Staging Slides 5

1.3 Display Size and Font Selection 7

1.4 Command-line Options 7

1.5 Printing 8

2 Making Slides **9**

2.1 Primary Slide Functions 9

2.2 Slide Registration 14

2.3 Viewer Control 15

2.4 Constants and Layout Variables 17

2.5 Configuration 19

2.6 Pict-Staging Helper 22

2.7 Text Formatting Helpers 23

2.8 Slides to Picts 24

3 Fullscreen vs. Widescreen Aspect Ratio **26**

3.1 Fullscreen Slides 26

3.2 Widescreen Slides 27

4 Typesetting Racket Code in Slideshow **30**

5 Animations **31**

5.1 Generating Animated Slides 31

6 Legacy Libraries **35**

Bibliography **36**

Index **37**

Index **37**

1 Creating Slide Presentations

The `slideshow` module acts as a language that includes:

- all of `racket` except for `printable<%>`;
- pict-creating functions from `pict`; and
- slide-composing functions from `slideshow/base`.

The `slideshow` and `slideshow/base` module initialization also check the `current-command-line-arguments` parameter to configure the slide mode (e.g., printing).

The rest of this section repeats information that is presented by the tutorial slideshow, which can be viewed by running the `slideshow` executable and clicking the Run Tutorial link.

1.1 Slide Basics

The main Slideshow function is `slide`, which adds a slide to the presentation with a given content. For example, the "Hello World" presentation can be defined by the following module:

```
#lang slideshow ; or slideshow/widescreen

(slide
 #:title "How to Say Hello"
 (t "Hello World!"))
```

The `t` function in this example creates a pict containing the given text using the default font and style.

Executing the above module pops up a slide-presentation window. Type Alt-q (or Meta-q) to end the slides. Here are more controls:

Alt-q, Meta-q, or Cmd-q	:	end slide show
Esc	:	if confirmed, end show
Right/Down arrow, Space, f, n, or click	:	next slide
Left/Up arrow, Backspace, Delete, or b	:	previous slide
g	:	last slide
1	:	first slide
s	:	next slide with a different title/name
a	:	previous slide starting different title/name
Alt-g, Cmd-g, or Meta-g	:	select a slide
Alt-p, Cmd-p, or Meta-p	:	show/hide slide number

Alt-c, Cmd-c, or Meta-c	:	show/hide commentary
Alt-d, Cmd-d, or Meta-d	:	show/hide preview
Alt-m, Cmd-m, or Meta-m	:	show/hide mouse cursor
Alt-l, Cmd-l, or Meta-l	:	show/hide “spotlight”
Shift with arrow	:	move window 1 pixel
Alt, Meta, or Cmd with arrow	:	move window 10 pixels

The `slide` function accepts any number of arguments. Each argument is a pict to be centered on the slide. The picts are stacked vertically with `(current-gap-size)` separation between each pict, and the total result is centered (as long as there's a gap of at least `(* 2 (current-gap-size))` between the title and content).

```
#lang slideshow

(slide
 #:title "How to Say Hello"
 (t "Hello World!")
 (t "Goodbye Dlrow!"))
```

Various functions format paragraphs and generate bulleted items for lists. For example, `item` creates a bulleted paragraph that spans (by default) the middle 2/3 of the slide:

```
#lang slideshow

(slide
 #:title "How to Say Hello"
 (item "If you want to create an example, you"
       "can always do something with" (bt "Hello World!"))
 (item "It's a bit silly, but a follow-up example"
       "could be" (bt "Goodbye Dlrow!")))
```

As the example illustrates, the `item` function accepts a mixture of strings and picts, and it formats them as a paragraph.

Changed in version 1.4: Added support for unmodified Up and Down arrow keys to behave like Left and Right arrow keys.

1.2 Staging Slides

The `slide` function creates a slide as a side effect. It can be put inside a function to abstract over a slide:

```
#lang slideshow
```

```
(define (slide-n n)
  (slide
   #:title "How to Generalize Slides"
   (item "This is slide number" (number->string n))))

(slide-n 1)
(slide-n 2)
(slide-n 3)
```

The `slide` function also has built-in support for some common multi-slide patterns. Each element argument to `slide` is usually a pict, but there are a few other possibilities:

- If an element is `'next`, then a slide is generated containing only the preceding elements, and then the elements are re-processed without the `'next`. Multiple `'next` elements generate multiple slides.
- If an element is `'alts`, then the next element must be a list of element lists. Each list up to the last one is appended to the elements before `'alts` and the resulting list of elements is processed. The last list is appended to the preceding elements along with the remaining elements (after the list of lists) and the result is re-processed.
- A `'nothing` element is ignored (useful as a result of a branching expression).
- A `'next!` element is like `'next`, except that it is preserved when condensing (via the `--condense` flag).
- A `'alts~` element is like `'alts`, except that it is *not* preserved when condensing.
- A comment produced by `comment` is ignored, except when commentary is displayed.

Here's an example to illustrate how `'next` and `'alts` work:

```
#lang slideshow

(slide
 #:title "Example"
 (item "First step")
 'next
 (item "Second step")
 'next
 'alts
 (list (list (item "Tentative third step")
             'next
             (item "This isn't working... back up"))
       (list (item "Third step that works")))
 'next
 (item "Fourth step"))
```

1.3 Display Size and Font Selection

Slideshow is configured for generating slides in either 1024 by 768 for fullscreen (4:3) mode or 1360 by 766 for widescreen (16:9) mode. When the current display has a different size as Slideshow is started, the Slideshow display still occupies the entire screen, and pictures are scaled just before they are displayed. Thus, one picture unit reliably corresponds to a "pixel" that occupies 1/1024 by 1/768 of the screen or 1/1360 by 1/766 of the screen.

Fullscreen versus widescreen mode is a property of an individual slide that can be selected using the `#:aspect` argument to `slide`, but the default is to adapt to a mode that the user selects with `--widescreen` or `--fullscreen`. See §3 "Fullscreen vs. Widescreen Aspect Ratio" for more information.

Beware that different font sets on different platforms can change the way a slide is rendered. For example, the `tt` font on one platform might be slightly wider than on another, causing different line breaks, and so on. Beware also of using bitmaps in slides when the presentation screen's pixels do not exactly match the slide's drawing units. In that case, consider using `size-in-pixels` (with the caveat that the resulting picture will take up different amounts of the slide on different displays).

Finally, beware that the `text` form for generating text pictures attempts to take into account any expected scaling for the display when measuring text. (All Slideshow text functions, such as `t` and `item` are built on `text`.) On some devices, scaling the picture potentially causes a different font size to be used for drawing the slide—rather than bitmap-scaling the original font—and changing the font size by a factor of k does not necessarily scale all text dimensions equally by a factor of k. Modern displays and drawing libraries make this scaling compensation a smaller effect than it used to be, but using `current-expected-text-scale` parameter can sometimes improve text scaling.

1.4 Command-line Options

`(require slideshow/start)` package: `slideshow-exe`

The `slideshow` executable instantiates the `slideshow/start` module, which inspects the command line as reported by `current-command-line-arguments` to get another module to `require` for the slide content.The `slideshow/start` module also initializes variables like `printing?` and `condense?` based on flags supplied on the command line.

Thus, if the above example is in `"multi-step.rkt"`, then the command

```
slideshow multi-step.rkt
```

runs the slides.

If the module given to `slideshow` has a `slideshow` submodule, then `slideshow/start`

`requires` the `slideshow` submodule after `require`ing the module. If the module has no `slideshow` but has a `main` submodule, then the `main` submodule is `require`d.

The `slideshow` executable accepts a number of command-line flags. Use the `--help` flag to obtain a list of other flags.

1.5 Printing

The `-p` or `--print` command-line flag causes Slideshow to print slides instead of showing them on the screen using the current platform's printing system. The `-P` or `--ps` generates PostScript directly, while `-D` or `--pdf` generates PDF directly. By default, PS or PDF output is configured for paper output; use `-e` or `--not-paper` to produce output where each page's bounding box matches the slide bounds.

PS-to-PDF converters vary on how well they handle landscape mode. Here's a Ghostscript command that converts slides reliably (when you replace `"src.ps"` and `"dest.pdf"` with your file names):

```
  gs -q -dAutoRotatePages=/None -dSAFER -dNOPAUSE -dBATCH -
sOutputFile=dest.pdf -sDEVICE=pdfwrite -c .setpdfwrite -c "<</Ori-
entation 3>> setpagedevice" -f src.ps
```

2 Making Slides

```
(require slideshow/base)
```
package: slideshow-lib

The slideshow/base module, which is re-provided by slideshow, provides the functions for creating slides.

2.1 Primary Slide Functions

```
(slide [#:title title
        #:name name
        #:aspect aspect
        #:layout layout
        #:gap-size sep-gap-size
        #:inset inset
        #:timeout secs
        #:condense? condense?
        #:page-mode page-mode]
        element ...)              → void?
  title : (or/c #f string? pict?) = #f
  name : (or/c #f string?) = title
  aspect : aspect? = #f
  layout : (or/c 'auto 'center 'top 'tall) = 'auto
  sep-gap-size : real? = (current-gap-size)
  inset : slide-inset? = (make-slide-inset 0 0 0 0)
  secs : (or/c #f real?) = #f
  condense? : any/c = (and secs #t)
  page-mode : (or/c 'none 'epoch 'all) = (current-page-mode)
  element : (flat-rec-contract elem/c
              (or/c pict-convertible?
                    'next 'next! 'alts 'alts~ 'nothing
                    comment?
                    (listof (listof elem/c))))
```

Creates and registers a slide. See §1.2 “Staging Slides” for information about *element*s. Multiple *element* picts are separated by *sep-gap-size* vertical space.

When this function is first called in non-printing mode, then the viewer window is opened. Furthermore, each call to the function yields, so that the viewer window can be refreshed, and so the user can step through slides. If the user closes the slide window, then slide triggers an error unless set-allow-new-slides-after-close! was called with a true value before the window was closed.

If *title* is not #f, then a title is shown for the slide. The *name* is used in the slide-navigation

dialog, and it defaults to *title*.

If *layout* is 'top, then the content is top-aligned, with (* 2 *sep-gap-size*) space between the title and the content. The 'tall layout is similar, but with only *sep-gap-size* space. The 'center mode centers the content (ignoring space consumed by the title). The 'auto mode is like 'center, except when *title* is non-#f and when the space between the title and content would be less than (* 2 *sep-gap-size*), in which case it behaves like 'top.

The *inset* argument supplies an inset that makes the slide-viewing window smaller when showing the slide. See make-slide-inset for more information.

If *secs* argument for #:timeout is not #f, then the viewer automatically advances from this slide to the next after *secs* seconds, and manual advancing skips this slide.

If *condense?* is true, then in condense mode (as specified by the -c command-line flag), the slide is not created and registered, but the page number is still incremented according to *page-mode*,

The *page-mode* argument determines how the slide call increments the page number. If *page-mode* is 'all, then every step for the slide increments the page number. If *page-mode* is 'none, the all steps for the slide use the same page number, and the next slide call also starts with the same page number. If *page-mode* is 'epoch, then it is equivalent to 'all if the timeout *secs* is #f or equivalent to 'none otherwise.

Changed in version 1.5 of package slideshow-lib: Added the #:aspect argument.
Changed in version 1.10: Added the #:page-mode argument.

```
(t str) → pict?
  str : string?
```

The normal way to make plain text. Returns (text *str* (current-main-font) (current-font-size)).

```
(it str) → pict?
  str : string?
```

The normal way to make italic text. Returns (text *str* (cons 'italic (current-main-font)) (current-font-size)).

```
(bt str) → pict?
  str : string?
```

The normal way to make bold text. Returns (text *str* (cons 'bold (current-main-font)) (current-font-size)).

```
(bit str) → pict?
  str : string?
```

Bold-italic text. Returns `(text str (list* 'bold 'italic (current-main-font)) (current-font-size))`.

```
(tt str) → pict?
  str : string?
```

The normal way to make monospaced text. Returns `(text str (current-tt-font) (or (current-tt-font-size) (current-font-size)))`.

Changed in version 1.9 of package `slideshow-lib`: Generalized to use `current-tt-font` and `current-tt-font-size`

```
(rt str) → pict?
  str : string?
```

The normal way to make serif text. Returns `(text str 'roman (current-font-size))`.

```
(titlet str) → pict?
  str : string?
```

Creates title text. Returns `((current-titlet) str)`.

```
(para [#:aspect aspect
       #:width width
       #:align align
       #:fill? fill?
       #:decode? decode?]
       element ...)       → pict?
  aspect : aspect? = #f
  width : real? = ((get-current-para-width #:aspect aspect))
  align : (or/c 'left 'center 'right) = 'left
  fill? : any/c = #t
  decode? : any/c = #t
  element : (flat-rec-contract elem/c
              (or/c string? pict-convertible? (listof elem/c)))
```

Generates a paragraph pict that is no wider than *width* units, and that is exactly *width* units if *fill?* is true. If *fill?* is `#f`, then the result pict is as wide as the widest line.

Each list within *element*s is spliced into the sequence of string and pict elements. If *decode?* is true, then strings among the *element*s are decoded by performing the following substitutions: `---` → `--`, `--` → `-`, ``` `` ``` → “, `''` → ”, `'` → ’. In addition, to better work with `at-exp` notation, if an *element* is `"\n"`, then it is dropped along with any spaces at the start of the next element.

Strings are split at spaces for word-wrapping to fit the page, and a space is added between elements. If a string element starts with one of the following punctuation marks (after decoding), however, no space is added before the string:

- ' , . : ; ? !) ” ’

The *align* argument specifies how to align lines within the paragraph.

See the spacing between lines is determined by the current-line-sep parameter.

Changed in version 1.5 of package slideshow-lib: Added the #:aspect argument.

```
(item [#:aspect aspect
       #:width width
       #:gap-size sep-gap-size
       #:bullet blt
       #:align align
       #:fill? fill?
       #:decode? decode?]
       element ...)            → pict?
  aspect : aspect? = #f
  width : real? = ((get-current-para-width #:aspect aspect))
  sep-gap-size : real? = (current-gap-size)
  blt : pict? = (scale bullet (/ sep-gap-size gap-size))
  align : (or/c 'left 'center 'right) = 'left
  fill? : any/c = #t
  decode? : any/c = #t
  element : (flat-rec-contract elem/c
              (or/c string? pict-convertible? (listof elem/c)))
```

Like para, but with *blt* followed by (/ *sep-gap-size* 2) space appended horizontally to the resulting paragraph, aligned with the top line. The paragraph width of *blt* plus (/ *sep-gap-size* 2) is subtracted from the maximum width of the paragraph.

Changed in version 1.5 of package slideshow-lib: Added the #:aspect argument.

```
(subitem [#:aspect aspect
          #:width width
          #:gap-size sep-gap-size
          #:bullet blt
          #:align align
          #:fill? fill?
          #:decode? decode?]
          element ...)            → pict?
  aspect : aspect? = #f
  width : real? = ((get-current-para-width #:aspect aspect))
  sep-gap-size : real? = (current-gap-size)
```

```
  blt : pict? = (scale o-bullet (/ sep-gap-size gap-size))
  align : (or/c 'left 'center 'right) = 'left
  fill? : any/c = #t
  decode? : any/c = #t
  element : (flat-rec-contract elem/c
              (or/c string? pict-convertible? (listof elem/c)))
```

Like `item`, but an additional `(* 2 sep-gap-size)` is subtracted from the paragraph width and added as space to the left of the pict. Also, `o-bullet` is the default bullet, instead of `bullet`.

Changed in version 1.5 of package `slideshow-lib`: Added the `#:aspect` argument.

```
(clickback pict thunk) → pict?
  pict : pict?
  thunk : (-> any)
```

Creates a pict that embeds the given one, and is the same size as the given pict, but that when clicked during a presentation calls *thunk*.

```
(interactive pict proc) → pict?
  pict : pict?
  proc : (frame% . -> . (-> any))
```

Creates a pict that embeds the given one, but that creates a floating frame at the pict's location on the screen during a presentation. After the floating frame is created (and before it is shown), *proc* is applied to the frame. The result from *proc* must be a procedure that is called when the window is removed (because the slide changes, for example).

```
(size-in-pixels pict [#:aspect aspect]) → pict?
  pict : pict?
  aspect : aspect? = #f
```

Scales *pict* so that it is displayed on the screen as `(pict-width pict)` pixels wide and `(pict-height pict)` pixels tall. The result is *pict* when using a 1024 by 768 display with a fullscreen aspect or when using a 1360 by 766 display with a widescreen aspect.

Changed in version 1.5 of package `slideshow-lib`: Added the `#:aspect` argument.

```
(pict->pre-render-pict pict) → pict?
  pict : pict?
```

Produces a pict that is like *pict*, but optimized for drawing on some platforms (currently Mac OS). This function may be useful to reduce drawing times for for large bitmaps or complex drawings.

Added in version 1.1 of package `slideshow-lib`.

```
(make-outline  name
               title
               subitems ...
              [#:aspect aspect]) → (symbol? . -> . void?)
  name : (or/c symbol? (listof symbol?))
  title : (or/c string? pict?)
  subitems : (or/c #f null?
                   (symbol? . -> . pict?))
  aspect : aspect? = #f
```

Returns a function that takes a symbol and generates an outline slide.

The ... above applies to all three arguments together. Each trio of arguments defines a section for the outline:

- The section *name* is either a symbol or a list of symbols. When the outline function is called later to make an outline, the given symbol is compared to the section's symbol(s), and the section is marked as current if the symbol matches.
- The *title* is used as the displayed name of the section.
- The *subitems* are displayed when the section is active. It can be `#f` or `null` (for historical reasons) if no subitems are to be displayed. Otherwise, it should be a function that takes a symbol (the same one passed to the outline maker) and produces a pict.

Changed in version 1.5 of package `slideshow-lib`: Added the `#:aspect` argument.

```
(comment text ...) → comment?
  text : (or/c string? pict?)
```

Combines strings and picts to be used as a slide element for (usually hidden) commentary. Use the result as an argument to `slide`.

```
(comment? v) → boolean?
  v : any/c
```

Returns `#t` if *v* is a comment produced by `comment`.

2.2 Slide Registration

```
(slide? v) → boolean?
  v : any/c
```

Returns `#t` if *v* is a slide produced by `most-recent-slide` or `retract-most-recent-slide`.

```
(most-recent-slide) → slide?
```

Returns a slide structure that may be supplied to `re-slide` to make a copy of the slide or `slide->pict` to re-extract the entire slide as a pict.

```
(retract-most-recent-slide) → slide?
```

Cancels the most recently created slide, and also returns a slide structure that may be supplied to `re-slide` to restore the slide (usually in a later position).

```
(re-slide slide [pict]) → void?
  slide : slide?
  pict : pict? = (blank)
```

Re-inserts a slide, `lt-superimpose`ing the given additional *pict*.

```
(slide->pict slide) → pict?
  slide : slide?
```

Converts a complete slide to a `pict`. The bounding box of the result corresponds to the slide within its margins.

2.3 Viewer Control

```
(start-at-recent-slide) → void?
```

Sets the starting slide for the talk to the most recently created slide. If this function is used multiple times, the last use overrides the earlier uses.

```
(enable-click-advance! on?) → void?
  on? : any/c
```

Enables or disables slide advance as a result of a mouse click.

```
(set-use-background-frame! on?) → void?
  on? : any/c
```

Enables or disables the creation of a background frame, which is typically useful only when `make-slide-inset` is used. The last enable/disable before the first slide registration takes effect once and for all.

```
(set-page-numbers-visible! on?) → void?
  on? : any/c
```

Determines whether slide numbers are initially visible in the viewer.

```
(current-page-number-font) → (is-a?/c font%)
(current-page-number-font font) → void?
  font : (is-a?/c font%)
```

Parameter that determines the font used to draw the page number (if visible).

```
(current-page-number-color) → (or/c string? (is-a?/c color%))
(current-page-number-color color) → void?
  color : (or/c string? (is-a?/c color%))
```

Parameter that determines the color used to draw the page number (if visible).

```
(current-page-number-adjust) → (-> number? string? string?)
(current-page-number-adjust proc) → void?
  proc : (-> number? string? string?)
```

Parameter that controls the precise text that appears to indicate the page numbers (if visible). The input to the function is the default string and the slide number, and the result is what is drawn in the bottom right corner. The default parameter value just returns its second argument.

```
(set-spotlight-style! [#:size size
                       #:color color]) → void?
  size : (or/c #f (>=/c 0)) = #f
  color : (or/c #f string? (is-a?/c color%)) = #f
```

Adjusts the size and color of the "spotlight," which can be enabled in Slideshow as an alternative to the mouse. Note that the color normally should have alpha value less than 1 (to make it partially transparent). If *size* or *color* is `#f`, the corresponding setting is unchanged.

```
(set-allow-new-slides-after-close! on?) → void?
  on? : any/c
```

Sets whether new slides are allowed after the Slideshow window is closed by the user. By default, an attempt to register a new slide via `slide` after the window is closed triggers an error. Calling this function with `#t` enables new slides to start a new slideshow.

Added in version 1.3 of package `slideshow-lib`.

2.4 Constants and Layout Variables

```
(aspect? v) → boolean?
  v : any/c
```

Return `#t` if *v* is `'fullscreen`, `'widescreen`, or `#f`, otherwise returns `#f`.

A symbolic *v* selects a specific aspect, while `#f` as an aspect corresponds to a user-selected aspect through the `--widescreen` or `--fullscreen` flag.

See also §3 “Fullscreen vs. Widescreen Aspect Ratio”.

Added in version 1.5 of package `slideshow-lib`.

```
gap-size : 24
```

A width commonly used for layout.

```
(current-gap-size) → real?
(current-gap-size sep-gap-size) → void?
  sep-gap-size : real?
```

A parameter whose value is a width used for the separation between items by `slide`, the size and spacing of a bullet for `item`, the space between a slide title and content in `'tall` mode, etc. The default value is `gap-size`.

```
bullet : pict?
```

A filled bullet used by default by `item`.

It is either `(t "•")`, if that character is available in the font that `t` uses, or it uses an implementation similar to `o-bullet`, but not hollow (using `disk`, not `circle`).

```
o-bullet : pict?
```

A hollow bullet used by default by `subitem`.

It’s implementation is:

```
(baseless
 (cc-superimpose
  (circle (/ gap-size 2))
  (blank 0 gap-size)))
```

```
client-w
(get-client-w [#:aspect aspect]) → exact-nonnegative-integer?
  aspect : aspect? = #f
```

Produces the width of the display area, minus `margin`s for a given *aspect*, where `client-w` is equivalent to `(get-client-w)`. The result changes if the margin is adjusted via `set-margin!`.

Changed in version 1.5 of package `slideshow-lib`: Added `get-client-w`.

```
client-h
(get-client-h [#:aspect aspect]) → exact-nonnegative-integer?
  aspect : aspect? = #f
```

Produces the height of the display area, minus `margin`s for a given *aspect*, where `client-h` is equivalent to `(get-client-h)`. The result changes if the margin is adjusted via `set-margin!`.

Changed in version 1.5 of package `slideshow-lib`: Added `get-client-h`.

```
full-page
(get-full-page [#:aspect aspect]) → pict?
  aspect : aspect? = #f
```

Produces an empty pict that is the same size as the client area, which is like `(blank client-w client-h)`. The `full-page` form is equivalent to `(get-full-page)`.

Changed in version 1.5 of package `slideshow-lib`: Added `get-full-page`.

```
titleless-page
(get-titleless-page [#:aspect aspect]) → pict?
  aspect : aspect? = #f
```

Produces an empty pict that is the same size as the client area minus the title area in `'top` layout mode, which is like `(blank client-w (- client-h title-h (* 2 gap-size)))`. The `titleless-page` form is equivalent to `(get-titleless-page)`.

Changed in version 1.5 of package `slideshow-lib`: Added `get-titleless-page`.

```
margin
```

Produces a number that corresponds to the current margin, which surrounds every side of the slide. The client area for a slide corresponds to the display area (which is either 1024 by 768 or 1360 by 766) minus this margin on each side. The default margin is 20.

The margin can be adjusted via `set-margin!`.

```
title-h
```

Produces a number that corresponds to the height of a title created by `titlet`.

If `titlet` is changed via the `current-titlet` parameter, the title height should be updated via `set-title-h!`.

```
printing? : boolean?
```

The value is `#t` if slides are being generated for printed output, `#f` for normal on-screen display. Printing mode is normally triggered via the `--print` or `--ps` command-line flag.

```
condense? : boolean?
```

The value is `#t` if slides are being generated in condensed mode, `#f` for normal mode. Condensed mode is normally triggered via the `--condense` command-line flag.

2.5 Configuration

```
(current-font-size) → exact-nonnegative-integer?
(current-font-size n) → void?
  n : exact-nonnegative-integer?
```

Parameter that determines the font size used by `t`, `para`, etc. The default size is `32`.

```
(current-main-font) → text-style/c
(current-main-font style) → void?
  style : text-style/c
```

Parameter that determines the font used by `t`, `para`, etc. The default is platform-specific; possible initial values include `'swiss`, `"Verdana"`, and `"Gill Sans"`.

```
(current-tt-font) → text-style/c
(current-tt-font style) → void?
  style : text-style/c
```

Parameter that determines the font used by `tt`. The default is `'(bold . modern)`.

Added in version 1.9 of package `slideshow-lib`.

```
(current-tt-font-size) → (or/c #f exact-nonnegative-integer?)
(current-tt-font-size size) → void?
  size : (or/c #f exact-nonnegative-integer?)
```

Parameter that determines the font size used by tt. The default is #f, which causes tt to use current-font-size.

Added in version 1.9 of package slideshow-lib.

```
(current-line-sep) → exact-nonnegative-integer?
(current-line-sep n) → void?
  n : exact-nonnegative-integer?
```

Parameter that controls the amount of space used between lines by para, item, and subitem.

```
(current-para-width) → exact-nonnegative-integer?
(current-para-width n) → void?
  n : exact-nonnegative-integer?
(get-current-para-width [#:aspect aspect])
 → (parameter/c exact-nonnegative-integer?)
  aspect : aspect? = #f
```

Parameter that controls the width of a pict created by para, item, and subitem. The value of current-para-width is the same as (get-current-para-width).

Changed in version 1.5 of package slideshow-lib: Added get-current-para-width.

```
(current-title-color) → (or/c string? (is-a?/c color%))
(current-title-color color) → void?
  color : (or/c string? (is-a?/c color%))
```

Parameter used by the default current-titlet to colorize the title. The default is "black".

```
(current-slide-assembler) → ((or/c string? #f)
                             exact-nonnegative-integer?
                             pict?
                             . -> .
                             pict?)
(current-slide-assembler proc) → void?
  proc : ((or/c string? #f)
          exact-nonnegative-integer?
          pict?
          . -> .
          pict?)
```

Parameter whose value is a function for assembling slide content into a single pict. An assembling function takes: a title, a vertical space amount, and a pict for the slide content (not counting the title).

The default assembler uses titlet to turn a title string (if any) to a pict and uses the vertical space to put the title pict above the slide content. See also current-titlet and set-title-h!.

The result of the assembler is ct-superimposed with the client area, but the resulting pict might draw outside the client region to paint the screen margins, too.

The slide assembler is *not* responsible for adding page numbers to the slide; that job belongs to the viewer. See also current-page-number-font, current-page-number-color, and set-page-numbers-visible!.

```
(current-titlet) → (string? . -> . pict?)
(current-titlet proc) → void?
  proc : (string? . -> . pict?)
```

Parameter to configure titlet. The default is

```
(lambda (s)
  (colorize (text s (current-main-font) 40)
            (current-title-color)))
```

If this parameter is changed such that the result is a different height, then set-title-h! should be called to update the value produced by title-h, titleless-page, etc.

```
(set-margin! amt) → void?
  amt : real?
```

Changes the margin that surrounds the client area. See also margin.

```
(set-title-h! amt) → void?
  amt : real?
```

Changes the expected height of a title, which adjusts title-h, client-h, full-page, and titleless-page.

```
(make-slide-inset left-inset
                  top-inset
                  right-inset
                  bottom-inset) → slide-inset?
  left-inset : exact-nonnegative-integer?
  top-inset : exact-nonnegative-integer?
  right-inset : exact-nonnegative-integer?
  bottom-inset : exact-nonnegative-integer?
```

Creates a slide inset, which describes a number of pixels to inset the viewer for a slide on each side.

```
(slide-inset? v) → boolean?
  v : any/c
```

Returns `#t` if *v* is a slide inset created by `make-slide-inset`, `#f` otherwise.

```
(commentary-on-slide-font-size) → exact-positive-integer?
(commentary-on-slide-font-size size) → void?
  size : exact-positive-integer?
```

The font size used for commentary when passing

```
--commentary-on-slide
```

on the command-line.

```
(current-page-mode) → (or/c 'none 'epoch 'all)
(current-page-mode mode) → void?
  mode : (or/c 'none 'epoch 'all)
```

Determines the default `#:page-mode` argument for `slide`, `play`, and `play-n`.

Added in version 1.10 of package `slideshow-lib`.

2.6 Pict-Staging Helper

```
(require slideshow/step)
```
package: `slideshow-lib`

The `slideshow/step` library provides syntax for breaking a complex slide into steps that are more complex than can be handled with `'next` and `'alts` in a `slide` sequence.

```
(with-steps (id ...) body ...)
```

Evaluates the *body*s once for each *id*, skipping an *id* if its name ends with `~` and `condense?` is true. The results of the last *body* for each iteration are collected into a list, which is the result of the `with-steps` form.

Within the *body*s, several keywords are bound non-hygienically (using the first *body*'s lexical context):

- `(only? id)` — returns `#t` during the *id* step (i.e., during the evaluation of the *body*s for *id*), `#f` otherwise.
- `(vonly id)` — returns the identity function during the *id* step, `ghost` otherwise.

- `(only id then-expr)` returns the result of *then-expr* during the *id* step, `values` otherwise.
- `(only id then-expr else-expr)` returns the result of *then-expr* during the *id* step, the result of *else-expr* otherwise.
- `(before? id)` — returns `#t` before the *id* step, `#f` starting for the *id* and afterward.
- `(vbefore id)`, `(before id then-expr)`, or `(before id then-expr else-expr)` — analogous to `vonly` and `only`.
- `(after? id)` — returns `#t` after the *id* step, `#f` through the *id* step.
- `(vafter id)`, `(after id then-expr)`, or `(after id then-expr else-expr)` — analogous to `vonly` and `only`.
- `(between? a-id b-id)` — returns `#t` starting from the *a-id* step through the *b-id* step, `#f` otherwise.
- `(vbetween a-id b-id)`, `(between a-id b-id then-expr)`, or `(between a-id b-id then-expr else-expr)` — analogous to `vonly` and `only`.
- `(between-excel? a-id b-id)` — returns `#t` starting from the *a-id* step through steps before the *b-id* step, `#f` for the *b-id* step and afterward.
- `(vbetween-excl a-id b-id)`, `(between-excl a-id b-id then-expr)`, or `(between-excl a-id b-id then-expr else-expr)` — analogous to `vonly` and `only`.

`(with-steps~ (id ...) body ...)`

Like `with-steps`, but when `condense?` is true, then `expr` is evaluated only for the last *id* (independent of whether the name of the last *id* name ends in `~`).

2.7 Text Formatting Helpers

`(require slideshow/text)` package: `slideshow-lib`

This module provides conveniences functions for formatting text.

`(with-size size expr)`

Sets `current-font-size` to *size* while running *expr*.

Added in version 1.2 of package `slideshow-lib`.

`(with-scale scale expr)`

Multiplies current-font-size by scale while running expr.

Added in version 1.2 of package slideshow-lib.

```
(big text)
(small text)
```

Scale current-font-size by 3/2 or 2/3, respectively, while running text.

Added in version 1.2 of package slideshow-lib.

```
(with-font font expr)
```

Sets current-main-font to font while running expr.

Added in version 1.2 of package slideshow-lib.

```
(with-style style expr)
```

Adds style to current-main-font (via cons) while running expr.

Added in version 1.2 of package slideshow-lib.

```
(bold text)
(italic text)
(subscript text)
(superscript text)
(caps text)
```

Adds the attributes for bold, italic, superscript, subscript, or small caps text, respectively, to current-main-font while running text.

Added in version 1.2 of package slideshow-lib.

```
(blank-line) → pict?
```

Adds a blank line of the current font size's height.

Added in version 1.2 of package slideshow-lib.

2.8 Slides to Picts

```
(require slideshow/slides-to-picts)
```
package: slideshow-lib

```
(get-slides-as-picts  path
                      width
                      height
                      condense?
                     [stop-after
                      #:aspect aspect]) → (listof pict?)
  path : path-string?
  width : real?
  height : real?
  condense? : any/c
  stop-after : (or/c #f exact-nonnegative-integer?) = #f
  aspect : (or/c 'fullscreen 'widescreen) = inferred-aspect
```

Executes the Slideshow program indicated by *path* in a fresh namespace, and returns a list of picts for the slides. Each pict has the given *width* and *height*, and *condense?* determines whether the Slideshow program is executed in condense mode.

The *aspect* argument indicates which kinds of slides should full the *width* be *height* area, and slides in the other aspect are scaled to fit; the default for *aspect* is inferred from *width* and *height*. The *aspect* argument also sets the default aspect while loading *path*.

If *stop-after* is not `#f`, then the list is truncated after *stop-after* slides are converted to picts.

Changed in version 1.8 of package `slideshow-lib`: Added `#:aspect`.

3 Fullscreen vs. Widescreen Aspect Ratio

Fullscreen (4:3, 1024 by 768) versus widescreen (16:9, 1360 by 766) aspect mode is a property of an individual slide that can be selected using the `#:aspect` argument to `slide`. The `slideshow/widescreen` language provides a variant of `slide` that makes `'widescreen` the default value of `#:aspect`, while `slideshow/fullscreen` provides a variant of `slide` that makes `'fullscreen` the default.

When a slide's aspect is not specified, then it adopts an aspect that can be selected via the `--widescreen` or `--fullscreen` flag when Slideshow starts. (That selection can be made "sticky" as the default for future runs by using the `--save-aspect` flag.) Selecting an aspect also affects the values of `client-w`, `client-h`, `full-page`, and `titleless-page` from `slideshow`, but it does not affect the bindings from `slideshow/widescreen` or `slideshow/fullscreen`. Keep in mind that specifying `#:aspect` for `slide` does not affect the value of `client-w`, etc., for constructing the slide's content, but you can use `get-client-w`, etc., to obtain the aspect-specific metrics.

Use the `slideshow` language for slides and libraries that are meant to adapt to a user's selected aspect, and use `slideshow/fullscreen` or `slideshow/widescreen` for slides and libraries that assume specific values for a slide's drawing area.

3.1 Fullscreen Slides

`#lang slideshow/fullscreen` package: `slideshow-lib`

`(require slideshow/fullscreen/base)` package: `slideshow-lib`

The `slideshow/fullscreen/base` module is reprovided by the `slideshow/fullscreen` language along with `racket` and `pict`.

Added in version 1.5 of package `slideshow-lib`.

`slide : procedure?`

The same as `slide` from `slideshow/base`, but with `'fullscreen` as the default value of the `#:aspect` argument.

`para : procedure?`

The same as `para` from `slideshow/base`, but with `'fullscreen` as the default value of the `#:aspect` argument.

`item : procedure?`

The same as `item` from `slideshow/base`, but with `'fullscreen` as the default value of the `#:aspect` argument.

`subitem` : `procedure?`

The same as `subitem` from `slideshow/base`, but with `'fullscreen` as the default value of the `#:aspect` argument.

`make-outline` : `procedure?`

The same as `make-outline` from `slideshow/base`, but with `'fullscreen` as the default value of the `#:aspect` argument.

`size-in-pixels` : `procedure?`

The same as `size-in-pixels` from `slideshow/base`, but with `'fullscreen` as the default value of the `#:aspect` argument.

`client-w`

The same as `(get-client-w 'fullscreen)`.

`client-h`

The same as `(get-client-h 'fullscreen)`.

`full-page`

The same as `(full-page 'fullscreen)`.

`titleless-page`

The same as `(titleless-page 'fullscreen)`.

3.2 Widescreen Slides

`#lang slideshow/widescreen` package: `slideshow-lib`

(require slideshow/widescreen/base) package: slideshow-lib

The slideshow/widescreen/base module is reprovided by the slideshow/widescreen language along with racket and pict.

Added in version 1.5 of package slideshow-lib.

slide : procedure?

The same as slide from slideshow/base, but with 'widescreen as the default value of the #:aspect argument.

para : procedure?

The same as para from slideshow/base, but with 'widescreen as the default value of the #:aspect argument.

item : procedure?

The same as item from slideshow/base, but with 'widescreen as the default value of the #:aspect argument.

subitem : procedure?

The same as subitem from slideshow/base, but with 'widescreen as the default value of the #:aspect argument.

make-outline : procedure?

The same as make-outline from slideshow/base, but with 'widescreen as the default value of the #:aspect argument.

size-in-pixels : procedure?

The same as size-in-pixels from slideshow/base, but with 'widescreen as the default value of the #:aspect argument.

client-w

The same as (get-client-w 'widescreen).

`client-h`

The same as `(get-client-h 'widescreen)`.

`full-page`

The same as `(full-page 'widescreen)`.

`titleless-page`

The same as `(titleless-page 'widescreen)`.

4 Typesetting Racket Code in Slideshow

`(require slideshow/code)` package: `slideshow-lib`

The `slideshow/code` library provides all of the exports of `pict/code` and also initializes `get-current-code-font-size` to `current-font-size`.

5 Animations

```
(require slideshow/play)
```
package: slideshow-lib

The slideshow/play module provides tools for generating animations as multiple, automatically advanced slides.

Many of the tools are based on a function that takes a number between 0.0 and 1.0 inclusive and produces a pict. The pict produced for the input 0.0 is the starting image of the animation, and the pict produced for 1.0 is the ending image, while intermediate values produced intermediate images. For example,

```
(lambda (n)
  (cellophane (t "Hello") n))
```

corresponds to an animation that fades in the word “Hello.”

5.1 Generating Animated Slides

```
(play gen
      [#:steps steps
       #:delay delay-secs
       #:skip-first? skip-first?
       #:title title
       #:name name
       #:aspect aspect
       #:comment comment
       #:layout layout
       #:page-mode page-mode])   → void?
  gen : ((real-in 0.0 1.0) . -> . pict?)
  steps : exact-positive-integer? = (current-play-steps)
  delay-secs : real? = 0.05
  skip-first? : any/c = #f
  title : (or/c string? pict? #f
                ((real-in 0.0 1.0) . -> . (or/c string? pict? #f)))
        = #f
  name : (or/c string? #f
               ((real-in 0.0 1.0) . -> . (or/c string? #f)))
       = title
  aspect : aspect? = #f
  comment : (or/c comment? #f) = #f
  layout : (or/c 'auto 'center 'top 'tall) = 'auto
  page-mode : (or/c 'none 'epoch 'all) = (current-page-mode)
```

Generates *steps*+1 slides by calling *gen* on equally-spaced values from 0.0 (inclusive) to 1.0 (exclusive). Except for the first of the slides, each slide has a timeout of *delay-secs*, so that the next slide appears automatically.

Normally, play is called via play-n, which effectively calls *gen* on 1.0 without a timeout to complete the animation and stop the auto-advance of slides. The play-n function also manages with multi-step animations.

If *skip-first?* is #f, then one fewer slide is generated, because *gen* is not called on 0.0.

The *title*, *name*, *aspect*, *layout*, and *page-mode* arguments are passed on to slide, at least when *title* and/or *name* are not functions. When *title* or *name* is a function, the function is applied to the value used to produce the slide content, and the resulting title or name is passed on to slide.

The *comment* argument is used like a comment argument to slide.

In condensed mode (i.e., when condense? is #t), any slide that would be registered with a timeout is instead skipped.

Changed in version 1.7 of package slideshow-lib: Added the *aspect* argument.
Changed in version 1.10: Added the #:page-mode argument.

```
(play-n  gen*
         [#:steps steps
          #:delay delay-secs
          #:skip-first? skip-first?
          #:skip-last? skip-last?
          #:title title
          #:name name
          #:aspect aspect
          #:comments comment
          #:layout layout
          #:page-mode page-mode])   → void?
  gen* : (and/c (unconstrained-domain-> pict?)
                (λ (x) (number? (procedure-arity x))))
  steps : (list*of exact-positive-integer?
                   (or/c exact-positive-integer? '()))
        = (current-play-steps)
  delay-secs : real? = 0.05
  skip-first? : any/c = #f
  skip-last? : any/c = #f
  title : (or/c string? pict? #f
                ((real-in 0.0 1.0) . -> . (or/c string? pict? #f)))
        = #f
```

```
name : (or/c string? #f
            ((real-in 0.0 1.0) . -> . (or/c string? #f)))
     = title
aspect : aspect? = #f
comment : (list*of comment? (or/c comment? #f '())) = #f
layout : (or/c 'auto 'center 'top 'tall) = 'auto
page-mode : (or/c 'none 'epoch 'all) = (current-page-mode)
```

Generates a sequence of slides by calling *gen** with, for each of its arguments, numbers from 0.0 to 1.0. If *gen** accepts *n* arguments, then result is a sequence of animations with a pause (i.e., not auto-advanced) between each of *n* segments.

If *gen** accepts a single argument, then play-n is like play, except that *gen** is also called with 1.0 to generate a slide with no timeout. If *gen** accepts multiple arguments, then slides are generated by calling *gen** with the first argument varying from 0.0 to 1.0 while all other arguments are 0.0. Then, the first argument is held at 1.0 while the second argument varies from 0.0 to 1.0, and so on.

For example,

```
(play-n
 (lambda (n1 n2)
   (cellophane (t "Hello")
               (* n1 (- 1.0 n2)))))
```

generates an animation to fade in the word “Hello,” and then pauses for a manual advance, and then fades “Hello” back out.

If *skip-first?* is #t, then the very first slide of the sequence is skipped. Similarly, if *skip-last?* is #t, then the last slide of the sequence is skipped.

The *steps* argument controls how many steps happen in each phase on the animation. If it is a number, then that number is used for each phase. If it is a pair of two numbers, then the first number is used for the first phase, and the second number is used for the rest of the phases. Similarly, if it is (cons num_1 (cons num_2 num_3)), num_1 and num_2 are used for the first two phases and num_3 is used for the rest.

The elements of the *comment* argument are used like the *steps* argument, except passed as comments instead of used as step counts.

The *delay-secs*, *title*, *name*, *aspect*, *layout*, and *page-mode* arguments are passed on to play for each of the *n* segments of animation.

Changed in version 1.7 of package slideshow-lib: Added the *aspect* argument.
Changed in version 1.10: Added the #:page-mode argument.

```
(animate-slide element ...)
 → (() (listof (real-in 0.0 1.0)) . ->* . pict?)
  element : (flat-rec-contract elem/c
              (or/c pict? 'next 'alts
                    (listof (listof elem/c))))
```

Accepts slide content similar to `slide` with `'next` and `'alts` and produces a procedure suitable for use with `play-n`. The result is similar to using `slide`, but with fades for `'next` and `'alts` transitions (to better fit the style, perhaps, of surrounding animations).

```
(current-play-steps) → exact-positive-integer?
(current-play-steps n) → void?
  n : exact-positive-integer?
```

A parameter that determines the default number of steps used for a slide animation. The parameter's initial value is `10`.

Added in version 1.6 of package `slideshow-lib`.

6 Legacy Libraries

`(require slideshow/pict)` package: `slideshow-lib`

The `slideshow/pict` library re-exports `pict`.

`(require slideshow/code-pict)` package: `slideshow-lib`

The `slideshow/code-pict` library re-exports `pict/code`.

Bibliography

[Findler06] Robert Bruce Findler and Matthew Flatt, "Slideshow: Functional Presentations," *Journal of Functional Programming*, 16(4-5), pp. 583–619, 2006. `http://www.cs.utah.edu/plt/publications/jfp05-ff.pdf`

Index

animate-slide
Animations
aspect?
big
bit
blank-line
bold
bt
bullet
caps
clickback
client-h
client-h
client-h
client-w
client-w
client-w
Command-line Options
comment
comment?
commentary-on-slide-font-size
condense?
Configuration
Constants and Layout Variables
Creating Slide Presentations
current-font-size
current-gap-size
current-line-sep
current-main-font
current-page-mode
current-page-number-adjust
current-page-number-color
current-page-number-font
current-para-width
current-play-steps
current-slide-assembler
current-title-color
current-titlet
current-tt-font
current-tt-font-size
Display Size and Font Selection
enable-click-advance!
full-page
full-page
full-page
Fullscreen Slides
Fullscreen vs. Widescreen Aspect Ratio
gap-size
Generating Animated Slides
get-client-h
get-client-w
get-current-para-width
get-full-page
get-slides-as-picts
get-titleless-page
interactive
it
italic
item
item
item
Legacy Libraries
make-outline
make-outline
make-outline
make-slide-inset
Making Slides
margin
most-recent-slide
o-bullet
para
para
para
pict->pre-render-pict
Pict-Staging Helper
play
play-n
Primary Slide Functions
Printing
printing?
re-slide
retract-most-recent-slide

rt
set-allow-new-slides-after-close!
set-margin!
set-page-numbers-visible!
set-spotlight-style!
set-title-h!
set-use-background-frame!
size-in-pixels
size-in-pixels
size-in-pixels
slide
slide
slide
Slide Basics
Slide Registration
slide->pict
slide-inset?
slide?
Slides to Picts
slideshow
slideshow/base
slideshow/code
slideshow/code-pict
slideshow/fullscreen
slideshow/fullscreen/base
slideshow/pict
slideshow/play
slideshow/slides-to-picts
slideshow/start
slideshow/step
slideshow/text
slideshow/widescreen
slideshow/widescreen/base
Slideshow: Figure and Presentation Tools
small
Staging Slides
start-at-recent-slide
subitem
subitem
subitem
subscript
superscript
t
Text Formatting Helpers
title-h
titleless-page
titleless-page
titleless-page
titlet
tt
Typesetting Racket Code in Slideshow
Viewer Control
Widescreen Slides
with-font
with-scale
with-size
with-steps
with-steps~
with-style